



T/FIN. FLR.
 EL. 100'-11-1/4"±
 (MATCH EXIST.)

T/FDN. WALL
 EL. 100'-0"±

EXTERIOR GRADE
 EL. 99'-0"±

T/BASEMENT FIN. FLR.
 EL. 91'-4"±

SECTION B-B

1"=1'-0" (A101/A102)

3/4" T&G HARDWOOD FLOORING
 3/4" T&G SUBFLOOR

EXIST. FLOOR ASSY.
 2x10 @ 16" O.C.

1.5" RIGID INSULATION

CAVITY INSULATION

1/2" OSB AROUND PERIMETER

3/4" RIGID INSULATION

EXPANDING FOAM INSULATION

2" RIGID INSULATION

EXPANDING FOAM AROUND

EXISTING 8 or 12" CMU WALL

2x4 STUD @ 24" O.C.

R15 MIN. WOOL INSUL.

1/2" NON-PAPER-FACED GYPSUM BOARD

TROWEL ON ADHESIVE 90% COVERAGE

TREATED 2x4 BOTTOM PLATE

SILL SEALER

3/4" T&G SUBFLOOR
 (DRYCORE)

REMOVE/PATCH
 EXIST. CONC. SLAB
 EXPANDING FOAM AROUND

4" DRAIN TILE

STONE BACKFILL

THE PERIMETER
 OF LOOSELY CUT
 RIGID INSULATION

ELEVATION